

PQA-PortableUltra

CLASS A PORTABLE POWER QUALITY ANALYZER



Power Quality acc. to
IEC 61000-4-30 ed.3



- ✓ Modern Control
- ✓ Harmonic Analysis including 200Hz spectra, and 2kHz spectra (with PQA-PortableUltraH up to 500kHz)
- ✓ Power and Energy

- ✓ Disturbances
- ✓ Waveform Capture
- ✓ Symmetrical Components
- ✓ Phasor Measurement Unit (PMU)

The **PQA-PortableUltra** is an ultra-precise device that calculates the power quality parameters according to **EN50160**, meeting evaluation requirements according to the **IEC 61000-4-30 ed. 3** class A standard and others.

PQA-PortableUltra

CLASS A PORTABLE POWER QUALITY ANALYZER



→ Functionality

The firmware calculates power quality parameters according EN50160 and fully follows the requirements described in IEC 61000-4-30 ed. 3 Class A and others (61000-4-7, 61000-4-15).

Main measurement functions:

- ✓ U, I, P, Q, S, frequency, THD U, THD I, power factor, energies – AP, AQ, AS, APin, APout; all quantities are per phase and total
- ✓ Harmonics – U, I, P, Q up to 50th harmonic; U and I also as 200Hz spectra (0-9 kHz) and 2kHz spectra (0-68 kHz)
PQA-PortableUltraH model provides 2kHz spectra up to 500kHz
- ✓ Symmetrical components - three-phase system decomposition into a positive, negative, and zero component
- ✓ All quantities are calculated on 200 ms (10/12 period basis) according to IEC 61000-4-30 ed. 3
- ✓ Voltage quality according to EN50160, IEC 61000-4-30 ed. 3 Class A (U, freq., THD U, flicker, unbalance, harmonics)
- ✓ Voltage events according EN50160, IEC 61000-4-30 ed. 3 Class A (dip, swell, interruption – time, extrema, length)
- ✓ Waveform capture (transients) – in case of trigger, the device captures the waveform
- Trigger can be activated by selected quantities (U, I, P, Q, S, freq., PF) crossing specified limits
- Waveform means raw voltage/current signal with sampling rate at 9,6 k/19,2 k/57,6 k/124 k per second, waveform length is up to 60 periods, with pre-trigger up to 1.2 second
- PQA-PortableUltraH provides waveforms with up to 840kSa/s, stored waveform length is then limited to 60 seconds
- ✓ Disturbances – in case of trigger, the device captures the half-period RMS quantities
 - Trigger can be activated by selected quantities (U, I, P, Q, S, freq., PF) crossing specified limits
 - Capture contains half-period quantities of voltage, current, frequency, power etc. (sampling rate is 100/120 samples per second), capture length is up to 15 minutes, with pre-trigger up to 30 seconds

→ Technical Parameters

VOLTAGE INPUT

CHANNELS	4
INPUT RANGE	500 V (Measuring up to 1000 V)
ACCURACY	0.05 %
ISOLATION VOLTAGE	6 kV
IMPEDANCE	10 MOhm

CURRENT INPUT

CHANNELS	4
CURRENT CLAMPS	Clamps, Rogowski Coils
INPUT RANGE	Acc. to the sensors, typical 5 A for clamps, 3000 A for Rogowski Coils
ACCURACY	Clamps 0.1 %, Rogowski Coils 0.5 %

HARDWARE

DISPLAY	10", 800 cd, touchscreen
DATA STORAGE	250 GB
INTERFACES	USB, Ethernet, Wi-Fi
A/D CONVERSION	24-bit sigma-delta
TRANSIENT SAMPLING RATE	9.6 kSa/s, 19.2 kSa/s, 57.6 kSa/s, 124 kSa/s PQA-PortableUltraH: 500 kSa/s, 840 kSa/s
POWER SUPPLY	100 VAC - 240 VAC
BATTERY	2 hours, 100 Wh
CLASS	CATIV 300 V
OTHERS	
OPTIONAL INTERFACES	GPS, CAN RS-485, Analog inputs



averna.com ◉ North America ◉ Europe ◉ Asia

Averna is a trademark of Averna Technologies Inc. All other brand names, product names or trademarks belong to their respective holders. © 2024 Averna. All rights reserved. 08/2024